



★ **2698**  
GRAMS TO CUT  
**ASTM ANSI CUT LEVEL**  
**A5**

SIZE S M L XL 2XL

| EN388 | ABRASION    | 0 | 1 | 2 | 3 | 4 | X |
|-------|-------------|---|---|---|---|---|---|
|       | BLADE CUT   | 0 | 1 | 2 | 3 | 4 | 5 |
|       | TEARABILITY | 0 | 1 | 2 | 3 | 4 | X |
|       | PUNCTURE    | 0 | 1 | 2 | 3 | 4 | X |

DuPont™  
**Kevlar.**



# ARCRESISTER

## SPECIFICATION

- Fire Retardant crust tanned soft goatskin leather
- Black Nomex® interlock fabric at backside
- Kevlar® based ANSI A5 cut resistant lined inside
- Stitched with Kevlar® for maximum thread strength
- Keystone thumb design with straight fingers for flexibility
- Shirred elastic along with leather hemmed bottom
- Clutch fingers with hook and loop closure velcro tape

### FEATURES



CUT



WATERPROOF



ANTI-VIBRATION



COWHIDE

### APPLICATIONS



MECHANICAL



HANDLING



CARPENTRY



FRAME WORK

PLOT # 103, SECTOR 7A,  
KORANGI INDUSTRIAL AREA, KARACHI-PAKISTAN 74900  
[www.info@elite-leather.com](http://www.info@elite-leather.com) | Phone: 0334 3931 029

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.